

Name: Pro-Tek 30
Revision Date: 7/23/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

PRO-TEK 30

MOISTURE DISPLACING RUST PREVENTIVE

DESCRIPTION

Pro-Tek 30 is a solvent based, soft film rust preventive and moisture displacing fluid designed to provide excellent indoor protection. When applied, this formulation will leave a uniform light, greasy and protective oily film. Pro-Tek 30 is ideal for protecting parts and components after exposure to water containing processes such as machining, washing, cleaning or exposure to high humidity environments. Pro-Tek 30 will protect parts for up to 24 months indoors as well as provide up to 6 months outdoor protection in covered environments.

PROPERTIES

Appearance:	Light brown liquid
Film Type:	Oily greasy film
Dry Time @20°C:	75 Minutes
Odor:	Hydrocarbon
Film Thickness:	0.8-1.0 Micron
Density lbs/gal:	6.8
Indoor Protection:	Up to 24 months
Outdoor Protection:	Up to 6 months (covered)
Flash Point:	128°F
Water Displacing:	Yes
Paintable/Weldable:	No

FEATURES & BENEFITS

- Excellent moisture displacing properties
- Effectively penetrates cracks and crevices
- Stable film reduces run off
- Resists alkaline and acidic contaminants
- Excellent long term indoor protection
- Does not contain chlorinated solvents
- Improves process reliability

HEALTH AND SAFETY

See the most recent SDS which is available directly from ValCOOL, your local representative or authorized distributor. ValCOOL uses only raw materials not listed as carcinogenic by IRAC.

APPLICATION

Apply product as is by brush, sprayer or immersion to all surfaces needing protection. To maximize moisture displacement, apply by immersion or dip tank. Allow to air dry. Drying time is influenced by temperature, relative humidity and air circulation. Remove product with solvent or alkaline cleaner.