

Name: Pro-Tek AA
Revision Date: 7/23/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

PRO-TEK AA

HIGHLY EFFECTIVE ACID ATMOSPHERE RUST PREVENTIVE

DESCRIPTION

Pro-Tek AA is a solvent based, highly effective moisture displacing rust preventive designed for indoor use providing protection for up to 2 years. When applied, this formulation will leave a uniform greasy film that effectively dewateres making it ideal for use after machined or washed parts. Pro-Tek AA is highly effective where water or saline solution must be displaced from corrodible surfaces and the corrosion prevented or arrested. Pro-Tek AA excels in acid atmospheric conditions found in industrial environments.

PROPERTIES

| | |
|---------------------|----------------------|
| Appearance: | Clear brown liquid |
| Film Type: | Thin greasy film |
| Dry Time @20°C: | N/A |
| Odor: | Hydrocarbon |
| Film Thickness: | 0.5-1.2 Micron |
| Density lbs/gal: | 6.9 |
| Indoor Protection: | Up to 2 years indoor |
| Outdoor Protection: | 6 months (covered) |
| Flash Point: | 105°F |
| Water Displacing: | Yes |
| Paintable/Weldable: | No |

FEATURES & BENEFITS

- Highly effective in alkaline and acidic environments
- Excellent moisture displacing properties
- Does not contain chlorinated solvents
- Economical in application and easy to apply
- Effective on both ferrous and non-ferrous metals

HEALTH AND SAFETY

See the most recent SDS which is available directly from ValCOOL, your local representative or authorized distributor. ValCOOL uses only raw materials not listed as carcinogenic by IRAC.

APPLICATION

Apply product as is by brush, spray or immersion to all surfaces needing protection. To maximize moisture displacement, apply by immersion or dip tank. Allow to air dry. Drying time is dependent on temperature, relative humidity and air circulation. Remove product with solvent or alkaline cleaner.