

Name: Val-Sol Dry Moly Lubricant
Revision Date: 6/21/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

VAL-SOL DRY MOLY LUBRICANT

DRY LUBRICANT CONTAINING MOLY

DESCRIPTION

Val-Sol Dry Moly Lubricant forms a thin, quick-drying film that provides clean, long-wearing lubrication and protection. It withstands extreme pressures and temperatures. Dry Moly Lubricant requires little or no surface preparation and adheres to most substrates and quickly reduces metal to metal contact, and is fast drying with minimal transfer.

FEATURES & BENEFITS

- Non-Corrosive
- Adheres to most substrates
- Repels dust and dirt
- Greatly enhances operating efficiency
- Requires little or no surface preparation
- Quick drying film
- Withstands extreme pressures and temperatures

APPLICATION

- Lock Mechanisms
- Chains
- Conveyors
- Tumbler Locks
- Gaskets
- Pump Assemblies
- Exposed Metal Parts
- Ovens
- Pistons
- Wire Ropes
- Tracks
- Windows
- Threaded Parts
- Pipe
- Cables
- Sprockets
- Sliding Doors
- Hinges
- Gears
- Drives
- Equipment

DIRECTIONS FOR USE

Made for areas servicing high temperatures (-28°F/33°C-600°F/315°C)

Shake can vigorously before use. Clean surface thoroughly. Keep can 6 to 8 inches away from surface and apply evenly. Thin coats are preferable. Set 1 to 5 minutes for best drying. The solids in this product may clog nozzle. Shake often while using.

PROPERTIES

| | |
|-------------------|-------------------|
| Appearance: | Gray Spray |
| Form: | Liquid |
| Vapor Density: | Heavier than air |
| Evaporation Rate: | Slower than ether |
| Odor: | Solvent |
| Flammability: | Level 3 Aerosol |
| Can Size: | 16 oz. |
| Net Weight: | 12 oz. |

HEALTH AND SAFETY

See the most recent SDS which is available directly from ValCOOL, your local representative or authorized distributor. ValCOOL uses only raw materials not listed as carcinogenic by IRAC.