

Name: Val-Sol Gel Lube
Revision Date: 6/21/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

VAL-SOL GEL LUBE

PTFE PENETRATING GEL LUBRICANT

DESCRIPTION

Val-Sol Gel Lube is a transparent, high pressure lubricant with high adhesive strength. Combining natural and synthetic lubrication agents with a high molecular weight polymer (PTFE) makes this product one of the best available.

DIRECTIONS FOR USE

Shake well before use. Saturate area to be lubricated. If necessary, repeat application.

FEATURES & BENEFITS

- Last longer than convectional lubricants
- Withstands severe temperatures
- Prevents sticking and freezing of rubber and metal
- Works in -30°F – 600°F
- Prevents rust and corrosion
- Resists water washout

PROPERTIES

Appearance:	Clear Spray
Form:	Liquid
Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether
Odor:	Solvent
Flammability:	Level 3 Aerosol
Can Size:	20 oz.
Net Weight:	13 oz.

APPLICATION

- Door Hinges
- Open Gears
- Wire Rope
- Cables
- Chains
- Sprockets
- Conveyor
- Manifold Heat Valves

HEALTH AND SAFETY

See the most recent SDS which is available directly from ValCOOL, your local representative or authorized distributor. ValCOOL uses only raw materials not listed as carcinogenic by IRAC.