

Name: Val-Sol Red Spray Grease
Revision Date: 6/21/2018 – R1

ValCool, LLC
5230 Brittmoore Rd
Houston, TX 77041

VAL-SOL RED SPRAY GREASE

ALL PURPOSE RED SPRAY GREASE

DESCRIPTION

Val-Sol Red Spray Grease is a premium grade aluminum-complex lubricant. It provides deep penetrating action with long lasting protection. It will not break down, harden or separate at extreme pressures or temperatures. For industrial bearings, even in chemical service, electric motor shafts, truck and tractor fifth wheels, roller chains, agricultural hitches, heavy equipment bearings surfaces, cables, pulleys, automotive hinges and striker plates.

FEATURES & BENEFITS

- Sets quickly to a grease
- Prevents Rust
- Holds up under extreme pressures
- Temperature range -40°F - 575°F
- Resists water

APPLICATION

- Gears
- Cables
- Chains
- Bearings
- Industrial Equipment
- Construction Equipment

DIRECTIONS FOR USE

Shake well before using. Spray at 8 to 10 inches distance. Liquid will gel almost instantly. Gel dries to a grease in several minutes.

PROPERTIES

Appearance:	Red Spray
Form:	Liquid
Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether
Odor:	Petroleum
Flammability:	Level 3 Aerosol
Density:	0.71
Flash Point:	-157°F
Can Size:	16 oz.
Net Weight:	11.5 oz.

HEALTH AND SAFETY

See the most recent SDS which is available directly from ValCOOL, your local representative or authorized distributor. ValCOOL uses only raw materials not listed as carcinogenic by IRAC.